

ANTIFREEZE/COOLANT GUIDE



NITRITE FREE ELC

APPLICATION

Heavy duty and fleet engines, gasoline engines

COOLANT TYPE

OAT Organic Acid Technology

FORMULATION

NAPS free Nitrite-free 2EH-free

PRODUCT PH

8-9

RECOMMENDED CHANGE INTERVAL

1,600,000 km or
1,000,000 miles

MEETS/EXCEEDS


ASTM D3306, D6210,
D4985

AVAILABLE SIZES

Bulk,
1,000 L Tote,
208.2 L Drum,
4 X 3.78 L Case

RECOMMENDED/SUITABLE FOR USE WITH:

- › AS/NZS 2108.1:1997 Type A
- › AS/NZS 2108.2004 Type A
- › BMW Mercedes BLATT 325.0, 325.2
- › Case New Holland
- › Chrysler MS-9769, MS-7170
- › CID-A-A52624A
- › Cummins 14603, 3666132
- › DAF MAT 74002
- › Detroit Diesel DDC 7SE298, 93K217
- › DEUTZ DQC CB-14
- › Ford ESE-M97B44A, WSSM97B44D, WSS-M97B51-A1
- › Freightliner 48-22880, 48-25878
- › GM 6277M
- › GM Heavy Truck
- › International Truck & Engine
- › ITE/Navistar CEMS B-1 Type III-A, MPAPS B-1 Type III-A
- › JIS K2234
- › John Deere H24
- › Kenworth R026-170-97
- › Komatsu
- › Kubota - Kobelco
- › Mack 014GS17004, 014GS17009
- › MAN 324, 324 Type NF, 324 Type SNF
- › MB 326.3, DBL 7700
- › MTU MTL 5048
- › PACCAR
- › PACCAR CS0185
- › Peterbilt 8502.002
- › Scania TB1451
- › TMC RP 329, 338
- › US Fed A-A870-A
- › Volvo 12806
- › Volvo Heavy Truck
- › Volvo/Mack
- › VW TL 774G
- › Waukesha



*Prices subject to change without notice. Limited offer, while quantities last. Pictures are for illustrations only. Applicable taxes extra.